

TECHNICAL DATA SHEET

General description: Stitched quadriaxial fabric
Commercial name: GQX 1200 C - 1250 mm
Product ID: VQ500110000
TDS Version: 2/0

CONSTRUCTION

PLY SEQUENCE	FIBER tex	FIBER DENSITY ends/10cm	FIBER type	SQUARE WEIGHT g/m ²	TOLERANCE +/-
0°	1200	24	E or ECR direct roving	288	5,00%
+45°	300	72	E or ECR direct roving	305	5,00%
90°	600	48	E or ECR direct roving	288	5,00%
-45°	300	72	E or ECR direct roving	305	5,00%
STITCHING	11	24	Polyester	11	5,00%
TOTAL				1 197	5%

BASIC CHARACTERISTICS

	VALUE	UNIT	TOLERANCE
Total product width:	1270	mm	-5/+5
Nominal product width:	1250	mm	
Edge dimension each side:	10	mm	
Stitch gauge:	E6		
Stitch type:	TRIKOT		
Stitch length:	2,5	mm	
Roll length:	35	m	

SPECIFIC CHARACTERISTICS

PACKAGING

Each roll is packed individually in plastic foil and contains unique roll identification label. Individual rolls are placed on wooden palette and wrapped with stretch foil. Specific packaging requirements are matter of agreement with customer.

STORAGE AND TRANSPORT

It is requested to store the goods in dry and dustproof environment protected against direct sunlight. Storage and processing temperature has to be controlled within temperature limits from 15°C to 30°C and at relative humidity limits from 45% to 65%. It is recommended to temper material minimum 24 hours before use. Transport of goods shall be carried out by covered means of transport protected against leaking.

IMPORTANT

The above information is only for consideration and evaluation. The user shall determine the suitability of a product for his particular purpose and shall assume all risks and liabilities in connection herewith.

Issued by: A.Hulač Document is approved electronically **Date:** 1.6.2019